SPECIFICATION

IBM Docket No. STL9-2000-0055

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN that I, John R. Ehrman of Sunnyvale, California and citizen of the United States have invented new and useful improvements in

METHOD OF, SYSTEM FOR, AND COMPUTER PROGRAM PRODUCT FOR CREATING AND CONVERTING TO UNICODE DATA FROM SINGLE BYTE CHARACTER SETS, DOUBLE BYTE CHARACTER SETS, OR MIXED CHARACTER SETS COMPRISING BOTH SINGLE BYTE AND DOUBLE BYTE CHARACTER SETS

of which the following is a specification:

METHOD OF, SYSTEM FOR, AND COMPUTER PROGRAM PRODUCT FOR CREATING AND CONVERTING TO UNICODE DATA FROM SINGLE BYTE CHARACTER SETS, DOUBLE BYTE CHARACTER SETS, OR MIXED CHARACTER SETS COMPRISING BOTH SINGLE BYTE AND DOUBLE BYTE CHARACTER SETS

CROSS-REFERENCE TO RELATED APPLICATIONS

Application Serial Number _____, filed concurrently herewith on July 10, 2000 for **DATA STRUCTURE FOR CREATING, SCOPING, AND CONVERTING TO UNICODE DATA FROM SINGLE BYTE CHARACTER SETS, DOUBLE BYTE CHARACTER SETS, OR MIXED CHARACTER SETS COMPRISING BOTH SINGLE BYTE AND DOUBLE BYTE CHARACTER SETS (IBM Docket STL9-2000-0068)**, currently co-pending, and assigned to the same assignee as the present invention; and

Application Serial Number _____, filed concurrently herewith on July 10, 2000 for **METHOD OF, SYSTEM FOR, AND COMPUTER PROGRAM PRODUCT FOR SCOPING THE CONVERSION OF UNICODE DATA FROM SINGLE BYTE CHARACTER SETS, DOUBLE BYTE CHARACTER SETS, OR MIXED CHARACTER SETS COMPRISING BOTH SINGLE BYTE AND DOUBLE BYTE CHARACTER SETS (IBM Docket STL9-2000-0069)**, currently co-pending, and assigned to the same assignee as the present invention.

The foregoing copending applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1.   Field of the Invention

The present invention relates in general to coded character sets for representing characters in a computer program, and more particularly to a creation of Unicode characters by converting from non-Unicode characters.

2.   Description of the Related Art

Unicode is a new internationally standardized data encoding for character data which allows computers to exchange and process character data in any natural language text. Its most common usage is in representing each character as a sixteen-bit number. This is sometimes called a "double-byte" data representation as a byte contains eight bits.

Most existing computer hardware and software represents specific sets of characters in an eight-bit code, of which ASCII (American National Standard Code for Information Interchange) and EBCDIC (Extended binary-coded decimal interchange code) are typical examples. In such an eight-bit representation (also known as a single-byte representation), the limit of two-hundred-fifty-six (256) unique numeric values imposes a restriction on the set of distinct characters that may be encoded using the two-hundred-fifty-six distinct values. Thus, it is necessary to define different sets of encodings for each desired set of characters.

The chosen set of characters is called a "Character Set". Each member of the character set can be assigned a unique eight-bit numeric value ("Code Point") from the set of the two-hundred-fifty-six distinct values (Code Points). A group of assignments of characters and control function meanings to all available code points is called a "Code Page"; for example, the

1 assignments of characters and meanings to the two-hundred-fifty-six code points (0 through
2 255) of an 8-bit code set is a Code Page. The combination of a specific set of characters and a
3 specific set of numeric value assignments is called a "Coded Character Set". To distinguish
4 among the many different assignments of characters to codings, each Coded Character set is
5 assigned an individual identification number called a "Coded Character Set ID" (CCSID).

6

7   In situations involving ideographic scripts such as Chinese, Japanese, or Korean, a
8 hybrid or mixed representation of characters is sometimes used. Because the number of
9 ideographic characters greatly exceeds the two-hundred-fifty-six possible representations
10 available through the use of an eight-bit encoding, a special sixteen-bit encoding may be used
11 instead. To manage such sixteen-bit representations in computing systems and devices built for
12 eight-bit representations, two special eight-bit character codes are reserved and used in the
13 eight-bit-character byte stream to indicate a change of alphabet representation. Typically, a
14 string of characters will contain eight-bit characters in a single-byte representation. When the
15 first of the two special character codes (commonly called a "Shift-Out" character) is
16 encountered indicating a switch of alphabets, the bytes subsequent to the Shift-Out character
17 are interpreted as double-byte pairs encoded in the special sixteen-bit double-byte encoding.
18 At the end of the double-byte ideographic string, the other special eight-bit character code
19 (commonly called a "Shift-In" character) is inserted to indicate that the following eight-bit
20 bytes are to be interpreted as single-byte characters, as were those characters preceding the
21 "Shift-Out" character. This hybrid representation is sometimes also called a "double-byte
22 character set" (DBCS) representation. When such DBCS strings are mixed with SBCS
23 characters, the representation is sometimes called a "mixed SBCS/DCBS" representation.

24

25   Ideographic characters may also be represented as sixteen-bit characters in strings
26 without any SBCS characters other than the special initial "Shift-Out" and final "Shift-In"
27 character codes if they are used in a context where it is known that there are no mixtures of
28 eight-bit characters and sixteen-bit characters. Such usage is sometimes called "pure DBCS".
29 The Shift-Out and Shift-In codes are still required as the text of the remainder of the program

1   may use single-byte encodings.

2

3   To illustrate, assume that the "Shift-Out" character is represented by the character '<'

4   and that the "Shift-In" character is represented by the character '>'. Then each of the three

5   representations just described may be written as strings of these forms:

6   'abcDEF'   SBCS string

7   'AB<wxyz>CD'   mixed SBCS/DBCS string

8   '<wxyz>'   pure DBCS string

9

10   The actual computer storage representation of each of these three character formats

11   would generally be similar to the following representations. For example, the SBCS string

12   would generally appear in storage as follows:

```
              +---+---+---+---+---+---+
    'abcDEF'  | a | b | c | D | E | F |
              +---+---+---+---+---+---+
           Six bytes, one byte per character
```

18   The hexadecimal encoding of this string in a standard representation may appear as:

```
              +---+---+---+---+---+---+
              | 81| 81| 83| C4| C5| C6|
              +---+---+---+---+---+---+
```

22

23   After translation to Unicode, the same characters may be represented by the following bytes

24   (shown in hexadecimal encoding):

```
       +---+---+---+---+---+---+---+---+---+---+---+---+
       | 00  61| 00  62| 00  63| 00  44| 00  45| 00  46|
       +---+---+---+---+---+---+---+---+---+---+---+---+
           Twelve bytes, two bytes per character
```

1 Similarly, the computer storage representation of a mixed SBCS/DBCS string may

2 generally appear as follows where 'wxyz' represents the four bytes needed to encode the two

3 ideographic DBCS characters between the Shift-Out and Shift-In characters, and the '?' strings

4 indicate the specific encodings assigned to the representations of the DBCS characters:

```
                     +---+---+---+---+---+---+---+---+---+---+
'AB<wxyz>CD'         | A | B | < | ?? ?? | ?? ?? | > | C | D |
                     +---+---+---+---+---+---+---+---+---+---+
                                    Ten bytes
```

The hexadecimal encoding of this string in a standard representation may appear as follows

(wherein the Shift-Out and Shift-In characters have encodings X'0E' and X'0F' respectively):

```
                     +---+---+---+---+---+---+---+---+---+---+
                     | C1| C2| 0E| ??| ??| ??| ??| 0F| C3| C4|
                     +---+---+---+---+---+---+---+---+---+---+
```

When translated to Unicode, the same characters may be represented by the these bytes (shown

in hexadecimal encoding):

```
                  +---+---+---+---+---+---+---+---+---+---+---+
                  | 00  41| 00  42| ?? ?? | ?? ?? | 00  43| 00  44|
                  +---+---+---+---+---+---+---+---+---+---+---+
                  Twelve bytes, two bytes per character
```

Note that the Shift-Out and Shift-In characters have been removed, as they are not necessary in

the Unicode representation.

1   For the third type of character string containing pure DBCS characters, the computer

2   storage representation may appear as follows:

3   +---+---+---+---+---+---+
4   '<wxyz>' | < | ?? ?? | ?? ?? | > | Six bytes
5   +---+---+---+---+---+---+

6   The hexadecimal encoding of this string in a standard representation may appear as follows

7   (wherein the Shift-Out and Shift-In characters have encodings X'0E' and X'0F' respectively):

8   +---+---+---+---+---+---+
9 | 0E| ??| ??| ??| ??| 0F|
10   +---+---+---+---+---+---+

11

12   When translated to Unicode, the same characters would be represented by the these bytes

13   (shown in their hexadecimal encoding):

14   +---+---+---+---+
15 | ?? ?? | ?? ?? |
16   +---+---+---+---+
17   Four bytes, two bytes per character

18

19   In typical usage, many coded character sets are used to represent the characters of

20   various national languages. As computer applications evolve to support a greater range of

21   national languages, there is a corresponding requirement to encompass a great multiplicity of

22   "alphabets". For example, a software supplier in England may provide an account

23   management program to a French company with a subsidiary in Belgium whose customers

24   include people with names and addresses in Danish, Dutch, French, Flemish, and German

25   alphabets. If the program creates billings or financial summaries, it must also cope with a

26   variety of currency symbols. Using conventional technology, it may be difficult, or even

27   impossible, to accommodate such a variety of alphabets and characters using a single eight-bit

28   coded character set.

29

30   In other applications, a program may be required to present messages to its users in any

STL9-2000-0055   7

1 of several selectable national languages (this is often called "internationalization"). Creating

2 the message texts requires that the program's suppliers be able to create the corresponding

3 messages in each of the supported languages, which requires special techniques for handling a

4 multiplicity of character sets in a single application.

5

6 Unicode offers a solution to the character encoding problem, by providing a single

7 sixteen-bit representation of the characters used in most applications. However, most existing

8 computer equipment creates, manages, displays, or prints only eight-bit single-byte data

9 representations. In order to simplify the creation of double-byte Unicode data, there is a need

10 for ways to allow computer users to enter their data in customary single-byte, mixed

11 SBCS/DBCS, and pure DBCS formats, and then have it converted automatically to the double-

12 byte Unicode representation.

SUMMARY OF THE INVENTION

The present invention comprises a method, system, article of manufacture, and a computer program product for representing characters in a computer program, and more particularly to a creation of Unicode characters by converting from non-Unicode characters. A preferred embodiment of the present invention provides methods for specifying the types of constants whose character values are to be converted to Unicode; for specifying which code page or pages are used for specifying the character encodings used in the source program for writing the character strings to be converted to Unicode; and that can be used to perform conversions from SBCS, mixed SBCS/DBCS, and pure DBCS character strings to Unicode. A syntax suitable for specifying character data conversion from SBCS, mixed SBCS/DBCS, and pure DBCS representations to Unicode utilizes an extension to the conventional constant subtype notation. In converting the nominal value data to Unicode, currently relevant SBCS and DBCS code pages are used, as specified by three levels or scopes derived from either global options, from local AOPTIONS statement specifications, or from constant-specific modifiers. Global code page specifications apply to the entire source program. These global specifications allow a programmer to declare the source-program code page or code pages just once. These specifications then apply to all constants containing a request for conversion to Unicode. Local code page specifications apply to all subsequent source-program statements. These local specifications allow the programmer to create groups of statements containing Unicode conversion requests, all of which use the same code page or code pages for their source-character encodings. Code page specifications that apply to individual constants allow a very detailed level of control over the source data encodings to be used for Unicode conversion. The conversion of source data to Unicode may be implemented inherently to the translator (assembler, compiler, or interpreter) wherein it recognizes and parses the complete syntax of the statement in which the constant or constants is specified, and performs the requested conversion. Alternatively, an external function may be invoked by a variety of source language syntaxes which parses as little or as much of the source statement as its

1   implementation provides, and returns the converted value for inclusion in the generated

2   machine language of the object program. Alternatively, the conversion may be provided by the

3   translator's macro instruction definition facility.

4

5   One aspect of a preferred embodiment of the present invention provides for the

6   specification of the types of constants whose character values are to be converted to Unicode.

7

8   Another aspect of a preferred embodiment of the present invention provides for the

9   specification of which code page or pages are used for specifying the character encodings used

10   in the source program for writing the character strings to be converted to Unicode.

11

12   Another aspect of a preferred embodiment of the present invention performs

13   conversions from SBCS, mixed SBCS/DBCS, and pure DBCS character strings to Unicode.

14

15   Another aspect of a preferred embodiment of the present invention provides a syntax

16   suitable for specifying character data conversion from SBCS, mixed SBCS/DBCS, and pure

17   DBCS representations to Unicode utilizing an extension to the conventional constant subtype

18   notation.

19

20   Another aspect of a preferred embodiment of the present invention converts a nominal

21   value data to Unicode using currently relevant SBCS and DBCS code pages as specified by a

22   level or scope.

23

24   Another aspect of a preferred embodiment of the present invention provides a global

25   level or scope comprising a global code page specification which applies to an entire source

26   program.

27

28   Another aspect of a preferred embodiment of the present invention provides a local

29   level or scope comprising a local code page specification which applies to all subsequent

1   source-program statements.

2

3   Another aspect of a preferred embodiment of the present invention provides an

4   individual constant level or scope comprising a code page specification that applies to an

5   individual constant.

6

7   A preferred embodiment of the present invention has the advantage of providing ease of

8   Unicode data creation: data can be entered into a program using familiar and customary

9   techniques, and in the user's own language and preferred character sets, without having to know

10 any details of SBCS, DBCS, or Unicode character representations or encodings.

11

12   A preferred embodiment of the present invention has the further advantage of providing

13 an ability to handle multiple single-byte and double-byte input data encodings, each specific to

14 a national language or a national alphabet. Such input data may be written in several

15 convenient forms, such as SBCS, mixed SBCS/DBCS, and pure DBCS.

16

17   A preferred embodiment of the present invention has the further advantage of providing

18 a variety of scopes for specifying controls over source data representations and encodings,

19 such that the user has complete control over the range of these specifications, ranging from

20 global (applying to all requested conversions in the entire program), local (applying to a range

21 of statements containing data to be converted) to individual or constant-specific (applying to a

22 single instance of data to be converted).

23

24   A preferred embodiment of the present invention has the further advantage of providing

25 an open-ended design allowing easy addition of supported character sets, by simply providing

26 additional Mapping Tables for each supported character set, and without any need to modify

27 the internal logic of the translator (assembler, compiler, or interpreter) to be cognizant of such

28 added character sets and tables.

1   A preferred embodiment of the present invention has the further advantage of having no

2   dependence on operating system environments or run-time conversion services, which may or

3   may not be available in the environment in which character data in the source programs are

4   being converted to Unicode and translated to machine language.

5

6   A preferred embodiment of the present invention has the further advantage of providing

7   a special language syntax specifying constants to be converted to Unicode, creating no conflicts

8   with existing applications. This syntax is also a natural and intuitively familiar extension of the

9   existing syntax for specifying character constants.

10

11   A preferred embodiment of the present invention has the further advantage of having no

12   need to prepare nor accept programs written using Unicode characters, and no need for

13   special Unicode-enabled input/output devices or mapping software, because of the ease of data

14   creation and the variety of data formats described above.

15

16   A preferred embodiment of the present invention has the further advantage of providing

17   an ability to implement conversions in multiple ways to provide flexibility, including

18   implementations in the translator itself ("native" implementation), or by using macro or

19   preprocessor instructions, or by utilizing the translator's support for externally-defined and

20   externally-written functions.

21

22   A preferred embodiment of the present invention has the further advantage of providing

23   an ability to support normal sixteen-bit Unicode and Unicode UTF-8 character formats as the

24   results of converting any of the source data formats described above.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the Description of the Preferred Embodiment in conjunction with the attached Drawings, in which:

Figure 1 is a block diagram of a distributed computer system used in performing the method of the present invention, forming part of the apparatus of the present invention, and which may use the article of manufacture comprising a computer-readable storage medium having a computer program embodied in said medium which may cause the computer system to practice the present invention;

Figure 2 is a block diagram of a mapping table data structure preferred in carrying out a preferred embodiment of the present invention;

Figure 3 and **Figure 4** are flowcharts of method steps preferred in carrying out a preferred embodiment of the present invention; and

Figures 5, 6, and 7 are listings of computer program code which implements the method steps preferred in carrying out a preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring first to **Figure 1**, there is depicted a graphical representation of a data processing system **8**, which may be utilized to implement the present invention. As may be seen, data processing system **8** may include a plurality of networks, such as Local Area Networks (LAN) **10** and **32**, each of which preferably includes a plurality of individual computers **12** and **30**, respectively. Of course, those skilled in the art will appreciate that a plurality of Intelligent Work Stations (IWS) coupled to a host processor may be utilized for each such network. Each said network may also consist of a plurality of processors coupled via a communications medium, such as shared memory, shared storage, or an interconnection network. As is common in such data processing systems, each individual computer may be coupled to a storage device **14** and/or a printer/output device **16** and may be provided with a pointing device such as a mouse **17**.

The data processing system **8** may also include multiple mainframe computers, such as mainframe computer **18**, which may be preferably coupled to LAN **10** by means of communications link **22**. The mainframe computer **18** may also be coupled to a storage device **20** which may serve as remote storage for LAN **10**. Similarly, LAN **10** may be coupled via communications link **24** through a sub-system control unit/communications controller **26** and communications link **34** to a gateway server **28**. The gateway server **28** is preferably an IWS which serves to link LAN **32** to LAN **10**.

With respect to LAN **32** and LAN **10**, a plurality of documents or resource objects may be stored within storage device **20** and controlled by mainframe computer **18**, as resource manager or library service for the resource objects thus stored. Of course, those skilled in the art will appreciate that mainframe computer **18** may be located a great geographic distance from LAN **10** and similarly, LAN **10** may be located a substantial distance from LAN **32**. For example, LAN **32** may be located in Belgium while LAN **10** may be located within England

1   and mainframe computer **18** may be located in New York.

2

3   Software program code which employs the present invention is typically stored in the

4   memory of a storage device **14** of a stand alone workstation or LAN server from which a

5   developer may access the code for distribution purposes, the software program code may be

6   embodied on any of a variety of known media for use with a data processing system such as a

7   diskette or CD-ROM or may be distributed to users from a memory of one computer system

8   over a network of some type to other computer systems for use by users of such other systems.

9   Such techniques and methods for embodying software code on media and/or distributing

10   software code are well-known and will not be further discussed herein.

11

12   As will be appreciated upon reference to the foregoing, it may be desirable for a user to

13   develop a multi-lingual or multi-alphabet software application. For example, a user of a

14   software supplier in England may develop an account management program on a workstation

15   **12** for use on a French company's computer **26** wherein the French company has a subsidiary

16   in Belgium running a computer **28** which must process requests from users operating

17   computers **30**, each of which may be interfacing in a different language, such as Danish, Dutch,

18   French, Flemish, or German. The present invention provides character specification and

19   conversion capabilities to accommodate such a variety of alphabets and characters.

20

21   The following description of an assembler based preferred embodiment of the present

22   invention assumes familiarity with the assembly language described in "IBM High Level

23   Assembler for MVS & VM & VSE Language Reference, Release 3", IBM Manual Number

24   SC26-4940-02, and the assembler options and external function interfaces described in "IBM

25   High Level Assembler for MVS & VM & VSE Programmer's Guide, Release 3", IBM Manual

26   Number SC26-4941-02. While this preferred embodiment of the present invention is described

27   in the context of the IBM Assembler Language, it can apply to other language translators such

28   as assemblers, compilers, and interpreters.

1   The invention concerns the creation of Unicode data, not its processing. The invention
2   may be described in three ways:
3   A.   Methods for specifying the types of constants whose character values are to be
4   converted to Unicode;
5   B.   Methods for specifying which code page or pages are used for specifying the character
6   encodings used in the source program for writing the character strings to be converted
7   to Unicode.; and
8   C.   Methods that can be used to perform conversions from SBCS, mixed SBCS/DBCS,
9   and pure DBCS character strings to Unicode.

10

11   In the following descriptions, the terms "source" or "source string" refer to the
12   characters to be converted to Unicode, and "source code page" refers to the particular encoding
13   used to represent the source-string characters as numeric quantities. Similarly, the terms
14   "target" or "target string" refer to the set of Unicode characters into which the source string is
15   being converted.

16

17   **Standard Syntax**
18   The terminology of the IBM Assembler Language is used to specify character constants.
19   The DC ("Define Constant") instruction directs the Assembler to convert the characters
20   enclosed in apostrophes specified in the operand field to the proper machine language
21   representation:

22   DC C'...SBCS characters...'   Convert '...SBCS characters...' to the
23   proper machine language representation.
24   DC C'...SBCS and DBCS characters...'   Convert '...SBCS and DBCS characters...'
25   to the proper machine language
26   representation. Requires that the DBCS
27   option be specified.
28   DC G'...pure DBCS characters...'   Convert '...pure DBCS characters...' to the
29   proper machine language representation.

1   Requires that the DBCS option be

2   specified.

3

4   The DC (Define Constant) statement has this general form:

5   label DC (DUPLICATION_FACTOR)(TYPE)(MODIFIERS)'(NOMINAL_VALUE)'

6 where the parentheses simply delimit the various fields, and are not part of the syntax of the

7 statement. In general, only the TYPE and NOMINAL_VALUE fields are required. For

8 example, a statement defining a character constant could be written:

9   DC C'This is a character constant'

10 where the TYPE is indicated by the letter C.

11

12   In the general form of the DC statement, each of the parenthesized terms has the

13 following meanings:

14

15 1.   The optional DUPLICATION_FACTOR field specifies that the constant defined by the

16   following elements should be repeated a specified number of times. For example,

17   DC 3C'XYZ='

18   would generate a machine language constant from the character string

19   'XYZ=XYZ=XYZ=', containing three repetitions of the nominal value string 'XYZ='.

20

21 2.   TYPE specifies the type of encoding to be created for the values specified in the

22   NOMINAL_VALUE field. In a preferred embodiment of the present invention, types

23   of specific interest and applicability are Types C and G, for "Character" and "Graphic"

24   constants, respectively. Other TYPE values are used to indicate that the

25   NOMINAL_VALUE data should be converted to machine language data

26   representations such as binary integer, floating point, packed decimal, and others as

27   described in the "High Level Assembler Language Reference" citation.

28

29   The TYPE specification may also include a "subtype" specification to provide

1   additional refinements in the type of conversion to be performed. For example, the "D"

2   type indicates that the NOMINAL_VALUE is to be converted to an eight-byte floating

3   point representation; two subtypes are supported, such that "DH" indicates conversion

4   to hexadecimal floating point, and "DB" indicates conversion to binary floating point.

5

6   3.   MODIFIERS specify additional information to be used in creating the generated

7   machine language constant. A preferred embodiment of the invention is primarily

8   concerned with the "Length" modifier, which asserts the exact length required for the

9   generated data. An additional modifier may be used for specifying code pages to be

10   used in converting individual constants.

11

12   4.   NOMINAL_VALUE is the data to be converted. A preferred embodiment of the

13   present invention is concerned with character data in three forms: SBCS data, mixed

14   SBCS/DBCS data, and pure DBCS data.

15

16   **Literals**

17

18   Literals are a convenient form of declaring a constant in the immediate context of its

19 use. For example, to set the address of a character constant into General Purpose Register 2, a

20 programmer may write the "Load Address" (LA) instruction thus:

21   LA   2,=C'A Character Constant'

22 where the equal sign indicates to the assembler that the following operand is a literal constant.

23 The assembler effectively creates a hidden internal name for the constant, replaces the literal

24 operand in the statement by the internal name, and places the text of a statement defining the

25 constant labeled with the internal name in a designated (or default) place in the program. This

26 saves the programmer from having to write two statements, such as:

27   LA   2,Char_Const

28   - - - other statements

29   Char-Const DC C'A Character Constant'

1   Literals can easily be supported for all constant types described in this preferred

2   embodiment of the present invention, and will therefore not be discussed further; such support

3   is assumed throughout.

4

5   The assembler also supports specialized forms of character-like data called "self-

6   defining terms". These comprise decimal, binary, hexadecimal, character, and graphic (pure

7   DBCS) forms. The values of all self-defining terms are fixed and predefined by the assembler.

8   For example, the self-defining terms 193, B'11000001', X'C1', and C'A' are required to have

9   identical values. For this reason, no dependence on code page specifications can be allowed for

10   character or graphic self-defining terms, as their values would not be fixed.

11

12   In the IBM High Level Assembler, the syntactic character set consists of

13   (a) upper-case and lower-case letters;

14   (b) decimal digits; and

15   (c) the special characters: + - / * . , ( ) @ # _ & ' = blank.

16   (d) The syntactically significant alphabetic character "$" ("currency symbol") is not invariant

17   across EBCDIC code pages; the Assembler Language requires it to have encoding X'5B', or 91

18   decimal.

19

20   Other characters are invariant across code pages, but they are not syntactically

21   significant:

22   ; : ? " % < >

23

24   The invariance or non-invariance of various syntactic characters is not significant to this

25   preferred embodiment of the present invention, other than providing a vehicle for the proper

26   recognition of character strings to be converted to Unicode. The character set used in character

27   data may contain SBCS and DBCS character encodings from many possible code pages

28   without affecting the syntactic or semantic behavior of the program, because the contexts

29   specifying data to be converted to Unicode are limited and well defined.

1   This preferred embodiment supports the common programming practice that source

2   programs (symbols, operation codes, etc.) are always created using a syntactic character set,

3   which includes those characters needed by the assembler or other programming-language

4   translator to correctly parse and tokenize the elements of the source program, and to identify

5   those program elements specifically requesting conversion to Unicode. Conversion-specific

6   character data appears only in restricted contexts, between the enclosing apostrophes of the

7   CU-type or GU-type constants described below. Text to be converted may therefore be

8   encoded in any desired manner.

9

10   Although the preferred embodiment described uses the Extended Binary Coded

11   Decimal Interchange Code (EBCDIC) for all but character data, this invention applies to any

12   conventional character set used for creating programs, such as ASCII.

13

14

A. Source Data Specification Extensions for Unicode

17   A syntax suitable for specifying character data conversion from SBCS, mixed

18   SBCS/DBCS, and pure DBCS representation to Unicode utilizes the constant subtype notation

19   described above. To specify that the nominal value of character data is to be converted to

20   Unicode, a programmer may write:

21   DC CU'...SBCS data...'   Convert SBCS to Unicode

22   DC CU'...SBCS/DBCS data...'   Convert mixed SBCS/DBCS to Unicode

23   Requires DBCS option

24   DC GU'...pure DBCS data...'   Convert pure DBCS data to Unicode

25   Requires DBCS option

26   The first of these is called "pure SBCS data" or simply "SBCS data". The second is called

27   "mixed SBCS/DBCS data", or simply "mixed data". The third is called "pure DBCS data".

28

29   In the preferred embodiment using the IBM High Level Assembler, the second and third

STL9-2000-0055   20

1   of these examples require that the DBCS option be specified so that mixed SBCS/DBCS data is

2   recognized correctly, but other forms of recognition rules or syntaxes for the nominal value

3   could also be used.

4

5   Another language extension provided by the preferred embodiment defines a new

6   constant type specifically for Unicode by assigning a TYPE code 'U'. Thus, a constant to be

7   converted to Unicode may be written:

8   DC U'Text to be converted'

9   which could be equivalent in other respects to a constant of type C. If this form is chosen, an

10   additional type letter would also have to be assigned to accommodate pure DBCS data, by

11   analogy with the G-type constant. Because the assembler has already assigned a large range of

12   letters for constant types, the method using a 'U' subtype described above is more economical

13   in its use of the available set of type codes.

14

15   In converting the nominal value data to Unicode, the assembler uses the currently

16   relevant SBCS and DBCS code pages, as derived from global options or from local

17   AOPTIONS statement specifications, or from constant-specific modifiers, as described below.

18

19   As with other character-based data types, no particular data alignment in storage is

20   assumed. However, since Unicode data naturally occurs in two-byte (sixteen-bit) forms, data

21   alignment on two-byte boundaries could easily be supported if processing efficiencies indicate

22   that doing so would be beneficial.

23

24   To simplify usage of these new constant types, the syntax of CU-type and GU-type

25   constants preferably should be unchanged from the current language definition for C-type and

26   G-type constants. This allows users who are familiar with existing coding styles and

27   conventions (i.e., the syntax of C-type and G-type constants) to utilize this invention with

28   minimal additional effort.

B. Methods for Specifying Source Code Pages

There are three levels, or "scopes", at which source code pages can be specified:

1. Global code page specifications that apply to the entire source program: these "global" specifications allow the programmer to declare the source-program code page or code pages just once. These specifications then apply to all constants containing a request for conversion to Unicode.

2. Local code page specifications that apply to all subsequent source-program statements: these "local" specifications allow the programmer to create groups of statements containing Unicode conversion requests, all of which use the same code page or code pages for their source-character encodings. For example, a program might contain statements defining messages in each of several national languages; each grouping could be preceded by such a "local" code page specification that applies to all the statements of that group, until a subsequent local specification is provided that applies to the following group.

3. Individual constant code page specifications that apply to individual constants: these allow a very detailed level of control over the source data encodings to be used for Unicode conversion. For example, if a message in one national language must contain a segment written in a different national language, each segment of the message can specify the encoding used for its characters.

B.1. Global Source Code Page Specification

Global source code specifications apply to all DC ("Define Constant") statements in the source program to which Unicode conversion should be applied. These global specifications would typically be specified as "options" or "parameters" presented to the Assembler at the time it is invoked or initialized, so that the Assembler can set up any needed information that will apply to the entire source program translation.

1   The forms that such global source code specification options may take include:

2   CODEPAGE(nnn)   specifies a SBCS code page

3   CODEPAGE(nnn,nnn...)   specifies a set of SBCS code pages (Example 1)

4   CODEPAGE(nnn,sss)   specifies a SBCS code page and a DBCS code page

5   DBCS(sss)   specifies a DBCS code page and enables recognition of DBCS

6   data

7   DBCS(sss,sss,...)   specifies a set of DBCS code pages and enable recognition of

8   DBCS data   (Example 2)

9   DBCS(CODEPAGE(sss))   specifies a DBCS code page and enables recognition of DBCS

10   data

11 and so forth, where values such as nnn and sss are Coded Character Set IDs (CCSIDs).

12 Combinations and variations of the above, as well as abbreviations of the keywords, are equally

13 useful. Default code page values can also be specified at the time the Assembler is installed on

14 the user's system, allowing Unicode translations to be specified in the program without the

15 need for invocation or initialization options.

16

17 In addition to these "invocation" options, the preferred embodiment allows the user to

18 specify certain options to be included in the statements of the source program, using the

19 *PROCESS statement. Thus, any of the above option forms could be placed in the source

20 module with a statement like:

21   *PROCESS CODEPAGE(nnn)

22 and so forth, for all possible variations. An additional capability is provided with the

23 *PROCESS statement: if the OVERRIDE(...) option is specified, as in:

24   *PROCESS OVERRIDE(CODEPAGE(nnn))

25 With the OVERRIDE(...) option, the user can thereby specify that no matter what CODEPAGE

26 options are specified when the Assembler is invoked, the global CODEPAGE value or values

27 cannot be changed from the value(s) required to produce correct conversion of the constants in

28 the source program.

B.2. Local Source Code Page Specification

The IBM High Level Assembler provides a mechanism allowing users to make local adjustments or overrides to options that can also be specified "globally". This mechanism is the ACONTROL statement. For example, if the user wishes that the assembler not diagnose certain substring operations, the user may specify:

ACONTROL FLAG(NOSUBSTR)   (Assembler ignores possibly-invalid substring techniques)

--- statements with unusual substring coding techniques ---

ACONTROL FLAG(SUBSTR)   (Assembler resumes checking substring techniques)

The ACONTROL statement can be used to specify localized controls over the source code pages to be used for converting designated forms of character data to Unicode. For example, distinct groups of statements can be converted to Unicode from separate code pages as follows:

ACONTROL CODEPAGE(nnn)

--- statements with character data to be converted to

--- Unicode using code page with CCSID nnn

ACONTROL CODEPAGE(mmm)

--- statements with character data to be converted to

--- Unicode using code page with CCSID mmm

1   Alternatively, if it is desired to specify multiple code pages to be used in converting

2   constants in subsequent statements, the ACONTROL statements could be specified in

3   alternative forms, such as:

4   .* Example 3

5   ACONTROL CODEPAGE(nnn1,nnn2,...),DCBS(CODEPAGE(sss1,sss2,...))

6   --- statements with character data to be converted to Unicode

7   --- using code pages selected among the nnn and sss values

8   .* Example 4

9   ACONTROL CODEPAGE(mmm1,mmm2,...),DBCS(CODEPAGE(ttt1,ttt2,...))

10   --- statements with character data to be converted to Unicode

11   --- using code pages selected among the mmm and ttt values

12   Thus, all the various formats of "global" options could be specified on ACONTROL

13   statements.

14

15   In cases where the user wishes to revert from a local source code page specification to

16   the global source code page specification, the following special notation may be used:

17   ACONTROL CODEPAGE(*)   (Revert to global source code page specifications)

18

19   Later, conversion and implementation techniques are described that involve methods

20   that do not require direct implementation in the assembler itself, such as macro instructions and

21   external functions. To assist such methods, the assembler can capture information from the

22   options and/or ACONTROL statements in global system variable symbols. These system

23   variable symbols are a method whereby the assembler can provide environmental and status

24   information to macros and functions. In implementing conversion to Unicode data formats, the

25   assembler can capture the designations of current code pages in system variable symbols such

26· as:

27   &SYS_SBCS_CODEPAGE   current SBCS code page

28   &SYS_DBCS_CODEPAGE   current DBCS code page

29   The advantages of this increment in assembler capability will be illustrated below.

B.3. Specifying Source Code Page for Individual Constants

The most discriminating level of code page specification is at the level of an individual constant. This invention involves adding a novel modifier, -- P meaning "Code Page"--, to the existing syntax for specifying constants to provide information about the code page or code pages used to create the source data for the constant.

To provide code page specifications for individual constants, another novel form of modifier is introduced:

    DC CUP(nnn)'...SBCS data...'

which requests that the SBCS data provided using code page "nnn" be converted to Unicode.

    DC CUP(nnn,sss)'...mixed SBCS/DBCS data...'

requests that the mixed SBCS/DBCS data provided using code page "nnn" for the SBCS data and the code page "sss" for the DBCS data be converted to Unicode.

    DC GUP(sss)'...pure DBCS data...'

requests that the pure DBCS data provided using code page "sss" be converted to Unicode.

The above examples demonstrate the use of an explicit numeric specification of the value of the code page modifier. It is common practice in programming languages to use symbolic forms for important numeric quantities; this invention supports this technique. For example, if the statement:

    MyCodePage Equ 1148

is used to declare that the symbol "MyCodePage" is equivalent to the value 1148, then the following two statements will be treated identically:

    DC CUP(1148)'Text using code page 1148'

    DC CUP(MyCodePage)'Text using code page 1148'

Thus, uses of this invention are not limited to strictly numeric specification of CCSIDs in all programming contexts.

For situations where more than one SBCS or DBCS code page is currently available (as exemplified in Examples 1, 2, 3, and 4 above), individual constants could refer indirectly to one of the previously specified code pages using a special "indicator" notation to select the desired code page. For example, suppose the ACONTROL statement of Example 3 immediately preceded these constants:

        DC   CUP(=1)'Convert this with code page nnn1'
        DC   CUP(=2)'Convert this with code page nnn2'

The notations "=1" and "=2" are intended to indicate that the first and second code pages declared in the ACONTROL statement should apply to each respective constant. The choice of the "=" character is of course arbitrary, and could be any character not allowed in valid language symbols. This level of constant-specific code page specification could also be used with U-type constants, as described above. Additional modifiers (such as length) can also be supported without any modifications to the existing language rules or implementation within the assembler.

C. Conversion Techniques

Three alternative embodiments for implementing the conversion of source data to Unicode will be described:

1.   The implementation is inherent to the assembler itself: the assembler recognizes and parses the complete syntax of the statement in which the constant or constants is specified, and performs the requested conversion.

2.   The implementation is provided in the form of an external function that can be invoked by a variety of source language syntaxes. The external function can parse as little or as much of the source statement as its implementation provides, and return the converted value to the assembler for inclusion in the generated machine language of the object program.

3.   The implementation is provided by the assembler's macro instruction definition facility. Each of these implementation techniques will be illustrated below.

Mapping Tables

A key element of the conversion process is the Mapping Table. One mapping table is created for each source code page, as identified by its CCSID. Each mapping table contains the Unicode character corresponding to each single-byte or double-byte character in the specified coded character set, arranged in ascending order of the numeric encoding assigned to each source character, as illustrated in **Figure 2**.

A Mapping Table **280** typically consists of a fixed-length header **282** containing a number of fields identifying the table and its status, so that the assembler can verify that the correct table is being used for the requested conversion. Following the header are the Unicode characters **284, 286, ... and 288** in the exact order of the numeric encoding assigned to the corresponding source character.

Thus, the Unicode character corresponding to the source character having a numeric encoding value of 1 would be found at **286**. Similarly, the Unicode character corresponding to the source character having a numeric encoding value of k would be found at **288**.

A Mapping Table for a SBCS character set would typically have two-hundred-fifty-six Unicode character entries, while a mapping table for a DBCS character set could have as many as sixty-five-thousand-five-hundred-thirty-six (65536) Unicode character entries. If it is known that certain restrictions may be imposed on the range of encoding values permitted for the source characters, then the contents of the mapping tables can be optimized to take advantage of those restrictions. For example, typical DBCS character encodings do not permit assignment of numeric encoding values less than sixteen-thousand-seven-hundred-five (16705), so that mapping table entries would not be necessary for converting those encodings.

Note that for any given constant, either one or two mapping tables will be required for

1 converting the nominal value of the constant to Unicode. For SBCS and pure DBCS data, only

2 a single mapping table is needed; for mixed SBCS/DBCS data, two mapping tables are

3 required: one for the SBCS data and one for the DBCS data.

4

5 **Table 1** illustrates typical assignments of Coded Character Set IDs (CCSIDs)

6 commonly used for single-byte encodings of character sets in widespread use. Further details

7 may be found in the manual "IBM National Language Design Guide, Volume 2" (manual

8 number SE09-8002-03).

9

10

11 **Table 1**

12 **Examples of CCSIDs for Commonly Used SBCS Character Sets**

SBCS CCSID	DESCRIPTION
01140	USA, Canada, Netherlands, Portugal, Brazil, Australia, New Zealand (00037 with euro)
01141	Austria, Germany (00273 with euro)
01142	Denmark, Norway (00277 with euro)
01143	Finland, Sweden (00278 with euro)
01144	Italy (00280 with euro)
01145	Spain, Latin America (Spanish) (00284 with euro)
01146	United Kingdom (00285 with euro)
01147	France (00297 with euro)
01148	Belgium, Switzerland, International Latin-1 (00500 with euro)

1   **Table 2** shows examples of typical code pages used for DBCS data in pure DBCS or

2   mixed SBCS/DBCS contexts.

3

4

<div align="center">

Table 2

Examples of DBCS Code Pages Suitable for Unicode Conversion

</div>

DBCS CCSID	DESCRIPTION
00935	Simplified Chinese (S-Chinese) Host Mixed (including 1880 UDC and Extended SBCS)
00937	Traditional Chinese (T-Chinese) Host Mixed (including 6304 UDC and Extended SBCS)
04396	Japanese Host Double-Byte (including 1880 UDC) (User Definable Characters)
09125	Korean Host Mixed (including 1880 UDC)

C.1. Assembler Implementation

To adapt the CCSID of a mapping table to a format usable by internal or operating
system services to locate the required mapping table, the assembler can employ a variety of
methods. One such technique uses the observation that each CCSID is sixteen bits long, and
that its hexadecimal representation therefore contains exactly four hexadecimal digits. For
example, CCSID number 01148 is equivalent to the hexadecimal value X'047C'. If those four
hexadecimal digits are converted to character form, they can be attached to a standard prefix
and used as a module name. For example, in the IBM High Level Assembler, such a module
name could be created from a prefix 'ASMA' and a suffix given by the four hexadecimal digits,
in this case 'ASMA047C'. This constructed name can then be used as the name of the mapping
table in all service requests involving finding and loading the mapping table.

1   Referring now to **Figure 3** and **Figure 4**, the flowcharts illustrate the operations

2   preferred in carrying out the preferred embodiment of the present invention. In the flowcharts,

3   the graphical conventions of a diamond for a test or decision and a rectangle for a process or

4   function are used. These conventions are well understood by those skilled in the art, and the

5   flowcharts are sufficient to enable one of ordinary skill to write code in any suitable computer

6   programming language.

7

8   Referring first to **Figure 3**, the conversion proceeds as follows. After the start **302** of

9   the conversion program, the assembler establishes at process block **304** the code page or code

10   pages used in the source text for specifying the nominal value of the data to be converted to

11   Unicode. Thereafter, at decision block **306**, the assembler determines whether the mapping

12   tables needed for converting source data written in the source-data code pages are currently

13   available. If they are, the assembler proceeds to process block **314** to begin the conversion

14   process. Otherwise, if the mapping tables needed for the conversion are not currently available,

15   then the assembler at process block **307** uses standard operating system services to load the

16   appropriate mapping table. Thereafter, decision block **308** determines if the load of the

17   mapping table was successful. If for any reason the loading process fails, then the assembler at

18   process block **310** issues appropriate error messages and terminates its attempt to convert the

19   constant **312**.

20

21   Returning now to process block **314**, to begin the conversion process the assembler

22   parses the source string to determine the number of characters it contains. These source

23   characters can be SBCS or DBCS characters. The number of these characters is assigned to the

24   variable NCS. Then, at process block **316**, the assembler sets a counter "K" for characters from

25   the source string to 1. Thereafter, assembler process block **318** extracts the K-th character from

26   the source string. Using the binary value of the character (which will be an 8-bit value for

27   SBCS characters, and a 16-bit value for DBCS characters), assembler process block **320**

28   extracts the Unicode character from the mapping table that whose position corresponds to that

29   binary value. This extracted value is then stored in the K-th position of the target string, as

1   illustrated in **Figure 2**.

2

3   After each Unicode character is stored in the target string, assembler process block **322**

4   increases the value of K by one, and its new value is then compared to the number of characters

5   NCS by decision block **324**. If the value of K does not exceed the value of NCS, program

6   control is returned to process block **318** to obtain and convert the next source character. If the

7   value of K exceeds the value of NCS, then conversion of the constant is complete, and the

8   Unicode character string is placed in the machine language of the object file for the program by

9   process block **326**. Thereafter, the program ends at process block **312**.

10

11   The process of selecting source-string characters in process steps **316** through **324** of

12   **Figure 3** are described in greater detail in **Figure 4** to show how SBCS and DBCS source

13   characters are selected. The source string is assumed to have previously been validated for

14   syntactic and semantic correctness. After the start **402** of the scanning process, the scanning

15   process is initialized **404** by setting a scan pointer to the address of the first byte of the source

16   string, the nominal value of the constant. Initialization also sets a binary switch to indicate that

17   the scan will proceed initially in "Single-Byte" mode. This switch is also used to determine

18   which Mapping Table (SBCS or DBCS) should be used to translate source characters to

19   Unicode.

20

21   Thereafter, the byte pointed to by the scan pointer is checked by decision step **406** to

22   see if it is a "Shift-Out" character, indicating the start of a DBCS string. If the character is not a

23   Shift-Out character, program control proceeds to process step **408** which determines that the

24   source characters are part of an SBCS character set. Process step **408** also uses the source

25   character pointed to by the scan pointer as the index into the SBCS Mapping Table, as

26   indicated in process step **320** of **Figure 3**, to perform the translation of process step **410** which

27   translates the source character to Unicode. Thereafter, process step **412** increments the scan

28   pointer by one byte to point to the next byte of the source string. Decision step **414** then

29   determines if the scan pointer now points past the end of the source string. If the scan pointer

1   now points past the end of the source string, then the translation is complete, process step **416**,

2   and the assembler resumes normal statement processing, process step **418**.

3

4   Returning now to decision step **406**, if the byte pointed to by the scan pointer is a

5   "Shift-Out" character, then control proceeds to process step **420** which increments the scan

6   pointer by one byte, effectively discarding the "Shift-Out" character. The binary switch

7   described at process step **404** is also set by process step **420** to indicate DBCS mode, thereby

8   allowing selection of the current DBCS Mapping Table to perform the translation as illustrated

9   in **Figures 2** and **3**. Thereafter, process step **422** uses the two bytes pointed to by the scan

10 pointer as the source character. Process step **424** then translates this source character to

11 Unicode using the DBCS Mapping Table. After the translation of the DBCS two-byte

12 character, control proceeds to process step **426** which increments the scan pointer by two bytes

13 to step over the DBCS source character just translated. Decision step **428** tests the following

14 byte to determine if it is a "Shift-In" character, which would indicate the end of the DBCS

15 portion of the source string. If the tested byte is not a "Shift-In" character, then program

16 control returns to process step **422** to process the next DBCS source character. Otherwise, if

17 the byte tested by decision step **428** is a "Shift-In" character, then program control proceeds to

18 process step **430** which resets the binary switch to indicate that SBCS mode is now active.

19 Thereafter, program control passes to the previously described process step **412** which

20 increments the scan pointer by one byte, effectively discarding the "Shift-In" character.

21

22

23   **C.1.1. Length Modifiers**

24

25 The Length modifier is supported by the assembler for most constant types. For

26 character constants, it is written in the form:

27   DC   CL(m)'This is a Character Constant'

28 where the generated machine language object code for the constant is required to have length

29 exactly "m" bytes. This means that the character string in the nominal value field could either

1   be truncated (if m is smaller than the length of the nominal value string), or padded on the right

2   with blanks (if m is larger than the length of the nominal value string). In the case of Unicode

3   constants the implementation may or may not require that any length modifiers of the form:

4   DC   CUL(m)'...'

5   DC   GUL(m)'<...>'

6   must evaluate to even values of "m". If "m" is odd (indicating that a Unicode character does

7   not contain the expected 16 bits), a diagnostic may be given and corrective action may be

8   taken.

9

10

C.2. Implementation Using Macro Instructions

Many assembler programs support some form of "macro-instruction" capability that
allows the programmer to create new capabilities whose invocations resemble ordinary
instructions.

C.2.1. Macro Instruction to Perform Basic Checking

The most trivial level of Unicode support could be a macro instruction whose argument
is a character string of hexadecimal digits, in which the user has manually encoded the
representation of each Unicode character. The primary function of such a macro could be
validate that the argument string contains a multiple of four hexadecimal digits corresponding
to an integral number of Unicode characters, and that each group of four hexadecimal digits
corresponds to a true Unicode character. For example, a DCUX macro instruction could be
written such that the user might write:

        DCUX X'...hex data...'

            or

        DCUX '...hex data...'

            or

```
DCUX    ...hex_data...
```

and the macro could verify that the number of hexadecimal digits is a multiple of 4, and that

the Unicode characters are valid.

C.2.2. Macro Instruction to Perform Checking and Conversion

A more powerful technique for supporting the conversion of character data to Unicode

characters is to create a macro definition with internal logic that performs a mapping similar to

that illustrated in **Figures 3** and **4**. Implementation of such a macro definition could also

include any needed mapping tables within the body of the definition.

An advantage of using macro instructions is that they utilize the existing facilities of the

assembler, and therefore do not require changes to the internal operation of the assembler.

Their primary disadvantage is that macro definitions must be executed interpretively when

invoked, so they are slower than the same function implemented "natively" in the internal logic

of the assembler. They also require extra coding for each additional code page being

supported. Thus, macro instructions provide an excellent means for testing and validating

conversion concepts, as well as a rapid development tool for situations where generality and

speed are not critical.

In a typical implementation, a macro instruction would be defined in such a way that its

arguments include a character string to be converted to Unicode, and an implicit indication

(using the system variable symbols described above) or explicit indication (by providing a

descriptive argument) of the CCSID of the code page in which the character string is

represented. The macro instruction would then generate directly the machine language

constant containing the Unicode data.

There are many ways to use macros for Unicode conversions. To illustrate, suppose the

1 following syntax is defined:

2   DCU '...character data...',CODEPAGE=nnn,DBCS=sss

3 where the three operands have these meanings:

4 1.   The first operand, '...character data...', consists of the character data to be converted to

5   Unicode, enclosed in quotation marks recognizable by the macro processor.

6 2.   The second operand, CODEPAGE=nnn, specifies the SBCS code page used for

7   encoding the first operand. If omitted, this operand would imply a default value for the

8   code page.

9 3.   The third operand, if present, indicates that the first operand contains either mixed

10   SBCS/DBCS or pure DBCS data, and provides the code page in which the DBCS data

11   is encoded. If omitted, this operand would imply that the first operand contains only

12   SBCS data.

13

14   An implementation of such a macro instruction which may be used to create Unicode

15 character constants is illustrated in **Figures 5, 6,** and **7.** It does not support the third operand

16 described above, but is intended to illustrate how a macro instruction can be used for Unicode

17 conversions. The macro uses the default code page with CCSID 500, the same as that used by

18 the assembler for its syntactic character set plus other invariant characters. Extending the

19 macro to accept other code pages is straightforward.

20

21

22 **C.3. Implementation Using External Functions**

23

24

25   The High Level Assembler supports a powerful capability for calling externally-

26 provided functions that can perform a variety of processing operations. Using an external

27 function requires defining the function in such a way that the assembler can locate and call it

28 during the assembly process, passing data supplied by the program to the function, and

29 receiving values returned by the function. In the context of converting character data to

1   Unicode, a call to such a function could take a form such as the following:

2   &Returned_Val   SetCF   'Ext_Func','character data','other_parameters'

3   The symbol "&Returned_Val" is where the called function "Ext_Func" places its computed

4   value as calculated from the other arguments. These arguments would typically include the

5   character string to be converted to Unicode, the code page or code pages used in coding the

6   character data, and any other values that might be useful to the external function. In practice,

7   the returned value would normally be substituted into a character or hexadecimal

8   constant, which the assembler would then map directly into the machine language form of the

9   Unicode constant.

10

11   An external function has much of the flexibility of the assembler itself: it can access

12   mapping tables as needed, as well as any other services of the operating system environment in

13   which the assembler itself is executing. Any error conditions can be reported to the assembler

14   using a message passing interface.

15

16   Further implementations of Unicode conversions could use a mixture of macro

17   instructions and external functions, in such a way that the user writes a statement such as the

18   following:

19   DCUNI   '...character data...',CODEPAGE=37

20   and the macro instruction could then pass the character data, the code page CCSID, and any

21   other useful or necessary information to an external function to perform the required

22   conversion. It could also generate the character or hexadecimal constant directly, in such a way

23   that the above DCUNI instruction appears to be "native" to the assembler itself. Other

24   implementations using external functions are of course possible.

UTF-8

UTF-8 is a special version of the Unicode representation, chosen for its suitability for transmission over communication protocols designed for eight-bit characters. These protocols are sensitive to specific eight-bit codes (such as control characters) that could appear in a stream of valid sixteen-bit Unicode characters, and the transmission of normal Unicode data would very likely be distorted. To avoid this problem, the Unicode standard defines UTF-8 as a reversible mapping of sixteen-bit Unicode characters to a special string of one to four eight-bit bytes, such that none of the eight-bit bytes have special meanings to transmission protocols.

The assembler could easily provide conversion of SBCS, mixed SBCS/DBCS, and pure DBCS data to the UTF-8 representation, thus avoiding the need for possibly expensive run-time conversions for each item of Unicode data being transmitted. In terms of the previous discussion:

1. Specification of a request for UTF-8 conversion can be provided globally, using an assembler option such as UTF8, or an operand on a *PROCESS statement such as:

   *PROCESS UTF8

2. Specification of a request for UTF-8 conversion can be provided locally, using an operand of the ACONTROL statement, such as:

   ACONTROL UTF8

3. Specification of a request for UTF-8 for an individual constant can be provided by a modifier, such as:

   DC CUTF8'Characters to be converted to UTF-8'

Thus, it can be seen that all of the methods described above for specifying the scope of conversion to Unicode can be applied to the requirements for conversion to the UTF-8 representation. It should be noted that UTF-8 data is not required to occupy an even number of eight-bit bytes, so that possible checks and diagnostics for an even number of bytes would not apply. However, in situations where a length modifier causes improper truncation of a UTF-8 byte string, a diagnostic would be appropriate.

1   Using the foregoing specification, the invention may be implemented using standard

2   programming and/or engineering techniques using computer programming software, firmware,

3   hardware or any combination or sub-combination thereof. Any such resulting program(s),

4   having computer readable program code means, may be embodied within one or more

5   computer usable media such as fixed (hard) drives, disk, diskettes, optical disks, magnetic tape,

6   semiconductor memories such as Read-Only Memory (ROM), Programmable Read-Only

7   Memory (PROM), etc., or any memory or transmitting device, thereby making a computer

8   program product, i.e., an article of manufacture, according to the invention. The article of

9   manufacture containing the computer programming code may be made and/or used by

10   executing the code directly or indirectly from one medium, by copying the code from one

11   medium to another medium, or by transmitting the code over a network. An apparatus for

12   making, using, or selling the invention may be one or more processing systems including, but

13   not limited to, central processing unit (CPU), memory, storage devices, communication links,

14   communication devices, servers, input/output (I/O) devices, or any sub-components or

15   individual parts of one or more processing systems, including software, firmware, hardware or

16   any combination or sub-combination thereof, which embody the invention as set forth in the

17   claims. User input may be received from the keyboard, mouse, pen, voice, touch screen, or any

18   other means by which a human can input data to a computer, including through other programs

19   such as application programs, databases, data sets, or files.

20

21   One skilled in the art of computer science will easily be able to combine the software

22   created as described with appropriate general purpose or special purpose computer hardware to

23   create a computer system and/or computer sub-components embodying the invention and to

24   create a computer system and/or computer sub-components for carrying out the method of the

25   invention. Although the present invention has been particularly shown and described with

26   reference to a preferred embodiment, it should be apparent that modifications and adaptations

27   to that embodiment may occur to one skilled in the art without departing from the spirit or

28   scope of the present invention as set forth in the following claims.